

KEIM Blockweiß (Stain blocker) water based isolating primer for interior use



1. Product description

KEIM Blockweiß is a white pigmented water based priming coat with highly isolating properties.

2. Field of application

KEIM Blockweiß is used to prime interior surfaces which have a staining/bleeding tendency. KEIM Blockweiß is preferably used to isolate and block the bleeding of marks and stains from e. g. water, oil, tar, soot, smoke or coloured pen. The substrate must be sound, dry and clean before application.

3. Product properties

- Highly isolating
- Low-odour
- Aqueous
- Pigmented, very good hiding power

Material characteristics

- Specific weight: approx. 1.30 g/cm³
- Solids content: approx. 55%

Colour shade

White

4. Application instructions

KEIM Blockweiß is applied to interior surfaces with problematic stains and bleedings. Application is ideally done on visually connected areas in order to achieve homogeneous results.

A one-coat primer coat application may be sufficient. In case of intensive stains two up to three applications are recommended.

A drying time of at least 12 hours between the coats is required. A thorough drying of 24 hours is necessary prior to subsequent coating with KEIM interior paints. The application is to be done in sections.

Application conditions

During application and drying the ambient and substrate temperatures must be between + 8°C and + 30°C. The relative humidity should not exceed 75 %.

Consumption

For a sufficient isolating effect and depending on the substrate a quantity of 150 ml/m² and application is recommended.

Note

Stir material well before application. Do not apply on distemper paints. Do not mix with other paints or tinting pastes. Dilution with water will impair the isolating properties.

5. Packaging

2.5 l tin or 12.5 l bucket

6. Storage

Shelf life is 1 year if tightly sealed and stored under cool, dry, frost-free conditions.

7. Disposal

EC Waste Code No. 08 01 12

Any residues must be emptied out of containers before recycling.



8. Safety instructions

Provide appropriate protection for surfaces which are not to be coated (e.g. glass, natural stone, ceramics, wood etc.). Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Provide constantly good ventilation during application and drying. Protect the eyes and skin from splashes. Do not eat, drink or smoke during application. Keep out of reach of children.

Product code: M-DF 02

Please refer to EC Safety Data Sheet.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.

